


Richie Rail 20





Richie Rail 20 is a unique illuminated handrail system with a diameter of 42.4mm. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. The innovative sliding wall brackets allow minimal power feeds to the LED strip for simple installation. Richie Rail 20 is suitable for use on residential and commercial stairs and thoroughfares including accessible routes and exterior urban spaces. Richie Rail 20 can be supplied as a "plug-and-play" modular system, or as a seamless, fully welded system.

MOUNTING OPTIONS

Wall mounted

DIFFUSER OPTIONS

Opal

Clear

SUPER SERIES LED STRIP OPTIONS

Lumens per metre Watts per metre Colour temp. 270lm 2700K 280lm 2.6W 3000K

300lm 4000K 470lm 2700K 600lm 5W 3000K 640lm 4000K 1250lm 2700K 1270lm 11W 3000K 4000K 1400lm

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP65 and RGBW colour change.

- All lumen values refer to the bare LED strip. Losses through diffuser/profile are not represented. Consult photometric data.


- 5 year manufacturer's warranty on Super Series LED strip.



WBRR-SS




Handrail 316 stainless steel




EX-RR20-MSA



EC-RR20-SS Handrail end can




JN-ST-RR20-SS Straight joiner



JN-90-RR20-SS 90 degree joiner



JN-VD-RR20-SS



JN-VU-RR20-SS Variable joiner, up



Joiner tube, for welded systems only



JN-90-RR20-W-SS 90 degree joiner tube, for welded systems only



JN-180-RR20-W-SS 180 degree joiner tube, for welded systems only



EC-TUBE-20-SS End cap for blank tube, for welded systems only



PTBRR-SS Post top bracket



PTBRR-SS-A Adjustable post top bracket

ADDITIONAL INFORMATION

Commercial stairs, public stairs, accessible routes, exterior urban spaces. **Applications**

Installation Interior or exterior (with IP65 rated LED strip).

Materials 316 stainless steel rail and components, extruded aluminium, polycarbonate diffuser.

Satin 316 stainless steel. Finish

Light source LED ribbon strip.

24V DC - remote driver options ranging from 6W up to 320W. Power supply

Dimmable Various options available, please enquire.



