

## Offspring Profiles

## Richie Rail 17





Richie Rail 17 is a unique illuminated handrail system. CNC machined wall brackets provide a beautiful finish and make for quick installation. Hollow wall brackets conceal the power supply to the LED strip, and the low voltage input makes the handrail safe to touch. Richie Rail 17 is suitable for use on residential and commercial stairs and thoroughfares.

MOUNTING OPTIONS	DIFFUSER OPTIONS	SUPER SERIES LED STRIP OPTIONS		
Wall mounted	Opal	Lumens per metre	Watts per metre	Colour temp.
	Clear			2700K
		280lm	2.6W	3000K
		300lm		4000K
		470lm		2700K
		600lm	5W	3000K
		640lm		4000K
		1250lm		2700K
		1270lm	11W	3000K
		1400lm		4000K

LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP65 and RGBW colour change.
All lumen values refer to the bare LED strip. Losses through diffuser/ profile are not represented. Consult photometric data.
S year manufacturer's warranty on Super Series LED strip.





WBRR17-H-MSA-R

JN-ST-RR17











WBRR17-H-MSA-S

Wall bracket with square cover Wall bracket with round cover

Straight joiner

WBPBS-10 Wall bracket plasterboard spacer, 10mm

WBPBS-13 Wall bracket plasterboard spacer, 13mn


JN-90-RR17 90 degree bend

JN-V-RR17 Variable bend

Applications				
Installation				
Materials				
Finish				
Light source				
Power supply				
Dimmable				

Residential or commercial stairs, lift cars, accessways. Interior or exterior (with IP65 rated LED strip). Extruded aluminium body and components, polycarbonate diffuser. Natural silver anodised or custom powder coat colours. LED ribbon strip. 24V DC - remote driver options ranging from 6W up to 320W. Various options available, please enquire.





C00 . C27 Polar curve for 1890 lumen LED strip with opal diffuser.

