

Offspring Profiles

Sweet 16





The Sweet 16 profile is a powerful, compact uplight/downlight solution. With a single LED strip for downlighting and two for uplighting, Sweet 16 is ideal for applications where high output and low-glare is key, such as boardrooms, reception counters and kitchen islands. Sweet 16 can be wired with two independent, dimmable circuits to achieve the perfect amount of light. Both wire and rod suspension options are available.

MOUNTING OPTIONS	DIFFUSER OPTIONS
Rod suspended	Opal
Wire suspended	Clear
Wall mounted	

SUPER SERIES LED STRIP OPTIONS

Lumens per metre	Watts per metre	Colour temp.	Lumens
		2700K	2000lm
280lm	2.6W	3000K	2000lm
300lm		4000K	2130lm
470lm		2700K	2190lm
600lm	5W	3000K	2340lm
640lm		4000K	2460lm
1250lm		2700K	- LED strip (
1270lm	11W	3000K	distributor f
		4000K	on request, - All lumen
			profile are i

Lumens per metre	Watts per metre	Colour temp.
------------------	-----------------	--------------

000lm		2700K
000lm	17W	3000K
130lm		4000K
190lm		2700К
340lm	20.3W	3000K
460lm		4000K

- LED strip options vary depending on region – please consult your local distributor for more information. Other LED strip options are available on request, including IP65 and RGBW colour change.
- All lumen values refer to the bare LED strip. Losses through diffuser/ profile are not represented. Consult photometric data.
- 5 year manufacturer's warranty on Super Series LED strip.











SWK-V-2M / SWK-V-4M

SRK-3-S / SRK-3-W



SRK-8-S / SRK-8-W Rod suspension kit (rod not incl.)



ROD-0.5M / ROD-1M / ROD-2M WB-S16 Suspension rod - 0.5m, 1m, 2m Wall bracket



CB-S16-60-R-S / CB-S16-60-R-W Cable base 60. recessed

CB-S16-80-SM-S / CB-S16-80-SM-W Cable base 80, surface mount


Wire suspe

Rod suspension kit (rod pot incl.)

ADDITIONAL INFORMATION Kitchen islands, boardroom tables, reception counters, office spaces. **Applications**

Installation Interior only. Materials Extruded aluminium body, polycarbonate diffuser, aluminium end caps. Finish Natural silver anodised or custom powder coat. Light source LED ribbon strip. 24V DC - remote driver options ranging from 6W up to 320W. Power supply Dimmable Various options available, please enquire.





Polar curve for 3x1340 lumen LED strips with clear diffuser up and opal down.

